



## Typical Inspection Data:

Density @ 20°C	0.865 g/cm <sup>3</sup>
Viscosity @ 100°C	12.1 cSt
Flash Point	250°C
Pour Point	-21°C

## Classic 30

### Mineral

#### Official Approvals:

SAE 30

API SA

#### Product Features:

- A monograde mineral oil with no detergent additive pack for 4 stroke petrol engines. For use where an oil of this quality is recommended.
- Particularly designed for classic and vintage cars but also suitable for other applications requiring a "straight" or additive free SAE 30 motor oil.
- Helps get the car started in winter.
- Stabilises oil pressure at high temperatures.
- May be used in manually operated gearboxes of that period.

#### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.

#### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 22-06-2021

**Moove Lubricants Ltd.** Dering Way, Gravesend, Kent DA12 2QX, England.

Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: [sales@commaoil.com](mailto:sales@commaoil.com) [www.CommaOil.com](http://www.CommaOil.com)